



Air Conditioning Technical Data



EEDEN14-100

RXG-L

TABLE OF CONTENTS

RXG-L

1	Features	20
2	Specifications	21
	Nominal Capacity And Nominal Input	21
	Nominal Capacity And Nominal Input	21
	Nominal Capacity And Nominal Input	22
	Technical Specifications	23
	Electrical Specifications	24
3	Electrical data	25
4	Capacity tables	27
	Cooling/Heating Capacity Tables	27
5	Dimensional drawings	34
6	Centre of gravity	35
7	Piping diagrams	36
8	Wiring diagrams	37
	Wiring Diagrams - Single Phase	37
9	Sound data	38
	Sound Pressure Spectrum	38
10	Operation range	40

1 Features

- Seasonal efficiency values up to A+++
- Outdoor units for pair application
- Outdoor units are fitted with a swing compressor, renowned for its low noise and high energy efficiency
- Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall

1



Inverter



Outdoor unit
silent operation

2 Specifications

2-1 Nominal Capacity And Nominal Input				FTXG20LW/RXG20L	FTXG25LW/RXG25L	FTXG35LW/RXG35L	FTXG50LW/RXG50L
Cooling capacity	Min.	kW		1.3 (2)		1.4 (2)	1.7 (2)
		Btu/h		4,400 (2)		4,800 (2)	5,800 (2)
		kcal/h		1,120 (2)		1,200 (2)	1,460 (2)
	Max.	kW		2.8 (2)	3.0 (2)	3.8 (2)	5.3 (2)
		Btu/h		9,500 (2)	10,200 (2)	13,000 (2)	18,100 (2)
		kcal/h		2,410 (2)	2,580 (2)	3,270 (2)	4,560 (2)
Heating capacity	Min.	kW		1.3 (3)		1.4 (3)	1.7 (3)
		Btu/h		4,400 (3)		4,800 (3)	5,800 (3)
		kcal/h		1,120 (3)		1,200 (3)	1,460 (3)
	Max.	kW		4.3 (3)	4.5 (3)	5.0 (3)	6.5 (3)
		Btu/h		14,600 (3)	15,400 (3)	17,100 (3)	22,200 (3)
		kcal/h		3,700 (3)	3,870 (3)	4,300 (3)	5,590 (3)
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+++		A++	
		Pdesign	kW	2.30	2.40	3.50	4.80
		SEER		8.52	8.50	7.00	6.70
		Annual energy consumption	kWh	94	99	175	251
	Heating (Average climate)	Energy label		A++		A+	
		Pdesign	kW	2.10	2.70	3.00	4.60
		SCOP		4.60			4.24
		Annual energy consumption	kWh	639	821	913	1,519
	Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER		4.59 (1)		3.97 (1)	3.53 (1)
		COP		5.00 (1)	4.42 (1)	4.06 (1)	3.65 (1)
Annual energy consumption		kWh	250	262	441	680	
Energy label		Cooling	A				
		Heating	A				
Piping connections	Liquid	OD	mm	6			
	Gas	OD	mm	9.5		12.7	
	Drain	OD	mm	18			
	Heat insulation			Both liquid and gas pipes			
Current	Nominal running current (RLA) - 50Hz	Cooling	A	2.8 (6) / 2.7 (7) / 2.6 (8)	2.9 (6) / 2.8 (7) / 2.7 (8)	5.0 (6) / 4.8 (7) / 4.6 (8)	6.5 (6) / 6.2 (7) / 5.9 (8)
		Heating	A	2.8 (6) / 2.7 (7) / 2.6 (8)	4.4 (6) / 4.2 (7) / 4.0 (8)	5.5 (6) / 5.3 (7) / 5.1 (8)	7.4 (6) / 7.1 (7) / 6.8 (8)

Notes

- (1) EER/COP according to Eurovent 2012, for use outside EU only
- (2) Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m
- (3) Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m
- (4) SL: The silent fan level of the air flow rate setting
- (5) 220V
- (6) 230V
- (7) 240V

2-2 Nominal Capacity And Nominal Input				FTXG20LS/RXG20L	FTXG25LS/RXG25L	FTXG35LS/RXG35L	FTXG50LS/RXG50L
Cooling capacity	Min.	kW		1.3 (2)		1.4 (2)	1.7 (2)
		Btu/h		4,400 (2)		4,800 (2)	5,800 (2)
		kcal/h		1,120 (2)		1,200 (2)	1,460 (2)
	Max.	kW		2.8 (2)	3.0 (2)	3.8 (2)	5.3 (2)
		Btu/h		9,500 (2)	10,200 (2)	13,000 (2)	18,100 (2)
		kcal/h		2,410 (2)	2,580 (2)	3,270 (2)	4,560 (2)
Heating capacity	Min.	kW		1.3 (3)		1.4 (3)	1.7 (3)
		Btu/h		4,400 (3)		4,800 (3)	5,800 (3)
		kcal/h		1,120 (3)		1,200 (3)	1,460 (3)
	Max.	kW		4.3 (3)	4.5 (3)	5.0 (3)	6.5 (3)
		Btu/h		14,600 (3)	15,400 (3)	17,100 (3)	22,200 (3)
		kcal/h		3,700 (3)	3,870 (3)	4,300 (3)	5,590 (3)

2 Specifications

2

2-2 Nominal Capacity And Nominal Input				FTXG20LS/RXG20L	FTXG25LS/RXG25L	FTXG35LS/RXG35L	FTXG50LS/RXG50L
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+++		A++	
		Pdesign	kW	2.30	2.40	3.50	4.80
		SEER		8.52	8.50	7.00	6.70
		Annual energy consumption	kWh	94	99	175	251
	Heating (Average climate)	Energy label		A++		A+	
		Pdesign	kW	2.10	2.70	3.00	4.60
		SCOP		4.60		4.24	
Annual energy consumption		kWh	639	821	913	1,519	
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER		4.59 (1)		3.97 (1)	3.53 (1)	
	COP		5.00 (1)	4.42 (1)	4.06 (1)	3.65 (1)	
	Annual energy consumption		kWh	250	262	441	680
	Energy label	Cooling		A			
		Heating		A			
Piping connections	Liquid	OD	mm	6			
	Gas	OD	mm	9.5		12.7	
	Drain	OD	mm	18			
	Heat insulation		Both liquid and gas pipes				
Current	Nominal running current (RLA) - 50Hz	Cooling	A	2.8 (6) / 2.7 (7) / 2.6 (8)	2.9 (6) / 2.8 (7) / 2.7 (8)	5.0 (6) / 4.8 (7) / 4.6 (8)	6.5 (6) / 6.2 (7) / 5.9 (8)
		Heating	A	2.8 (6) / 2.7 (7) / 2.6 (8)	4.4 (6) / 4.2 (7) / 4.0 (8)	5.5 (6) / 5.3 (7) / 5.1 (8)	7.4 (6) / 7.1 (7) / 6.8 (8)

Notes

- (1) EER/COP according to Eurovent 2012, for use outside EU only
- (2) Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m
- (3) Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m
- (4) SL: The silent fan level of the air flow rate setting
- (5) 220V
- (6) 230V
- (7) 240V

2-3 Nominal Capacity And Nominal Input				FVXG25K/RXG25L	FVXG35K/RXG35L	FVXG50K/RXG50L
Cooling capacity	Min.	kW		1.3	1.4	1.7
		Btu/h		4,400	4,800	5,800
	Nom.	kW		2.5 (3)	3.5 (3)	5.0 (3)
		Btu/h		8,500 (3)	11,900 (3)	17,100 (3)
	Max.	kW		3.0	3.8	5.6
		Btu/h		10,200	13,000	19,100
Heating capacity	Min.	kW		1.3	1.4	1.7
		Btu/h		4,400	4,800	5,800
	Nom.	kW		3.4 (4)	4.5 (4)	5.8 (4)
		Btu/h		11,600 (4)	15,400 (4)	19,800 (4)
	Max.	kW		4.5	5.0	8.1
		Btu/h		15,400	17,100	27,600
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++		A
		Pdesign	kW	2.50	3.50	5.00
		SEER		6.53	6.48	5.41
		Annual energy consumption	kWh	134	189	324
	Heating (Average climate)	Energy label		A++		A+
		Pdesign	kW	2.80	3.10	4.60
		SCOP		4.65	4.00	4.18
		Annual energy consumption	kWh	842	1,087	1,543

2 Specifications

2-3 Nominal Capacity And Nominal Input				FVXG25K/RXG25L	FVXG35K/RXG35L	FVXG50K/RXG50L
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER			-		
	COP			-		
	Annual energy consumption kWh			-		
	Energy label	Cooling		-		
Heating		-				
Piping connections	Liquid	OD	mm	6		
	Gas	OD	mm	9.5		12.7

Notes

- (1) Energy label: scale from A (most efficient) to G (less efficient)
- (2) Annual energy consumption: based on average use of 500 running hours per year at full load (nominal conditions)
- (3) Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB
- (4) Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB
- (5) 220V
- (6) 230V
- (7) 240V
- (8) When connected with multi-system outdoor unit, refer to the specifications of the multi outdoor unit to be connected.

2-4 Technical Specifications					RXG20L	RXG25L	RXG35L	RXG50L		
Capacity control	Method				Inverter controlled					
Casing	Colour				Ivory white					
Dimensions	Unit	Height	mm		550		735			
		Width	mm		765		825			
		Depth	mm		285		300			
	Packed unit	Height	mm		612		797			
		Width	mm		906		992			
		Depth	mm		402		437			
Weight	Unit		kg		35		48			
	Packed unit		kg		38		52			
Packing	Weight		kg		3		4			
Heat exchanger	Length		mm		805		845			
	Rows	Quantity			2					
	Fin pitch		mm		1.4		1.8			
	Stages	Quantity			24		32			
	Tube type				ø7 Hi-XD		ø8 G2E			
	Fin	Type			Waffle louvered fin		Colgate fin			
	Compressor	Model				1YC23APXD		2YC36GXD		
Type				Hermetically sealed swing compressor						
Output		W		600		1,100				
Fan	Type				Propeller fan					
	Air flow rate	Cooling	High	m³/min	34.5		37.0		49.8	
				cfm	1,218		1,306		1,758	
			Super low	m³/min	31.0				42.6	
		cfm	1,094				1,504			
		Heating	High	m³/min	31.1				44.8	
				cfm	1,098				1,581	
	Super low		m³/min	26.4				38.3		
	cfm	932				1,352				
Fan motor	Model				D23H-28		KFD-380-50-8C			
	Output		W		23		53			
	Speed	Cooling	High	rpm	860		920		780	
				Super low	rpm		780		rpm	
		Heating	High	rpm	860				720	
				Super low	rpm		740		rpm	
Sound power level	Cooling		dBA		61		63			
	Heating		dBA		62		63			

2 Specifications

2

2-4 Technical Specifications					RXG20L	RXG25L	RXG35L	RXG50L
Sound pressure level	Cooling	High	dBA		46		48	
		Silent operation	dBA		43		44	
	Heating	High	dBA		47		48	
		Silent operation	dBA		44		45	44
Operation range	Cooling	Ambient	Min.	°CDB	-10 (5)			
			Max.	°CDB	46			
	Heating	Ambient	Min.	°CWB	-15			
			Max.	°CWB	18 (5)			
Refrigerant	Type				R-410A			
	Charge			kg	1.05		1.6	
	GWP				1,975			
Refrigerant oil	Type				FVC50K			
	Charged volume			l	0.375		0.395	
Piping connections	Liquid	OD	mm		6.35			
	Gas	OD	mm		9.5		12.7	
	Drain	ID	mm		-			
		OD	mm		18			
	Piping length	OU - IU	Max.	m	20		30	
		System	Chargeless	m	10			
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)			
Level difference	IU - OU	Max.	m	15		20		

2-5 Electrical Specifications					RXG20L	RXG25L	RXG35L	RXG50L
Power supply	Name				V1			
	Phase				1~			
	Frequency			Hz	50			
	Voltage			V	220-240			
Current	Nominal running current (RLA)	Cooling	A	2.68 (2) / 2.58 (3) / 2.48 (4)	2.78 (2) / 2.68 (3) / 2.58 (4)	4.84 (2) / 4.64 (3) / 4.44 (4)	6.34 (2) / 6.04 (3) / 5.74 (4)	
		Heating	A	2.65 (2) / 2.55 (3) / 2.45 (4)	4.24 (2) / 4.04 (3) / 3.84 (4)	5.29 (2) / 5.09 (3) / 4.89 (4)	7.19 (2) / 6.89 (3) / 6.59 (4)	
	Starting current	Cooling	A	2.8	4.4	5.5	7.4	
		Heating	A	2.8	4.4	5.5	7.4	
Current - 50Hz	Maximum fuse amps (MFA)		A	16		20		
Current - 60Hz	Maximum fuse amps (MFA)		A	-				
Wiring connections	For power supply	Remark		3 for power supply, 4 for interunit wiring (including earth wiring)				

Notes

- (1) SL: The silent fan level of the air flow rate setting
- (2) 220V
- (3) 230V
- (4) 240V
- (5) Operation range in combination with Nexura, FVXG-K, cooling: min. 10°CDB ~ max. 46°CDB; heating: min. -15°CWB ~ max. 18°CWB

3 Electrical data

3 - 1 Electrical Data

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXG20LV1BW FTXG20LV1BS	RXG20L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	40	2.4	23	0.23	40	0.15
							2.3				
							2.2				
FTXG25LV1BW FTXG25LV1BS	RXG25L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	42	2.6	23	0.23	40	0.15
							2.4				
							2.3				
FTXG35LV1BW FTXG35LV1BS	RXG35L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	68	4.7	23	0.23	40	0.15
							4.4				
							4.2				

3D086658

SYMBOLS

- MCA : Min. Circuit Amps (A)
- MFA : Max. Fuse Amps (A)
- RHz : Rated operating frequency (Hz)
- RLA : Rated Load Amps (A)
- OFM : Outdoor fan motor
- IFM : Indoor Fan Motor.
- FLA : Full Load Amps (A)
- W : Fan Motor Rated Output (W)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19°CWB
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FVXG25K2V1B	RXG25L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	47	2.6	23	0.23	32	0.16
							2.5				
							2.4				
FVXG35K2V1B	RXG35L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	9.75	16	72	4.4	23	0.23	32	0.16
							4.2				
							4.0				

3D072090B

SYMBOLS

- MCA : Min. Circuit Amps (A)
- MFA : Max. Fuse Amps (A)
- RLA : Rated Load Amps (A)
- OFM : Outdoor fan motor
- IFM : Indoor Fan Motor
- FLA : Full Load Amps (A)
- W : Fan Motor Rated Output (W)
- RHz : Rated operating frequency (Hz)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19°CWB
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.

3 Electrical data

3 - 1 Electrical Data

3

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FTXG50L18W FTXG50L18S	RXG50L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	19.75	20	66	6.1	53	0.27	40	0.15
							5.8				
							5.6				

3D086655

SYMBOLS

MCA : Min. Circuit Amps. (A)
MFA : Max. Fuse Amps (A)
RHz : Rated operating frequency (Hz)
RLA : Rated Load Amps. (A)
OFM : Outdoor fan motor
IFM : Indoor Fan Motor.
FLA : Full Load Amps. (A)
W : Fan Motor Rated Output (W)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19°CWB
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.

Representative unit combination		Power supply				Comp.		OFM		IFM	
Indoor unit	Outdoor unit	Hz-volts	Voltage range	MCA	MFA	RHz	RLA	W	FLA	W	FLA
FVXG50K2V1B	RXG50L2V1B	50 - 220 50 - 230 50 - 240	Max. 50Hz 264V Min. 50Hz 198V	19.75	20	70	6.7	53	0.27	32	0.16
							6.3				
							6.1				

3D072099C

SYMBOLS

MCA : Min. Circuit Amps (A)
MFA : Max. Fuse Amps (A)
RLA : Rated Load Amps (A)
OFM : Outdoor fan motor
IFM : Indoor Fan Motor
FLA : Full Load Amps (A)
W : Fan Motor Rated Output (W)
RHz : Rated operating frequency (Hz)

NOTES

1. RLA is based on the following conditions:
Indoor temp.: 27°CDB/19°CWB
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

FTXG20LV1BW + RXG20L2V1B FTXG20LV1BS + RXG20L2V1B

A	8.9
B	0.11

Cooling 50Hz 220-240V

Indoor		Outdoor temperature [°C DB]																	
C	D	20			25			30			32			35			40		
°C	°C	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	2.36	1.96	0.38	2.25	1.91	0.42	2.14	1.86	0.46	2.10	1.84	0.47	2.04	1.82	0.49	1.93	1.77	0.53
16.0	22	2.46	1.93	0.39	2.36	1.88	0.42	2.25	1.84	0.46	2.21	1.82	0.47	2.14	1.79	0.50	2.03	1.75	0.53
18.0	25	2.57	2.05	0.39	2.46	2.01	0.42	2.35	1.97	0.46	2.31	1.95	0.48	2.25	1.93	0.50	2.14	1.88	0.54
19.0	27	2.62	2.19	0.39	2.51	2.15	0.43	2.41	2.11	0.46	2.36	2.10	0.48	2.30	2.07	0.50	2.19	2.03	0.54
22.0	30	2.78	2.13	0.39	2.67	2.09	0.43	2.57	2.05	0.47	2.52	2.04	0.48	2.46	2.02	0.50	2.35	1.98	0.54
24.0	32	2.89	2.08	0.39	2.78	2.05	0.43	2.67	2.01	0.47	2.63	2.00	0.48	2.56	1.98	0.51	2.46	1.95	0.54

A	10.2
---	------

Heating 50Hz 220-240V

Indoor		Outdoor temperature [°C WB]									
D		-10		-5		0		6		10	
°C		E	G	E	G	E	G	E	G	E	G
15.0		1.68	0.42	1.97	0.44	2.25	0.46	2.59	0.49	2.81	0.51
20.0		1.60	0.43	1.88	0.45	2.16	0.48	2.50	0.50	2.73	0.52
22.0		1.56	0.44	1.84	0.46	2.13	0.48	2.47	0.50	2.69	0.52
24.0		1.53	0.44	1.81	0.46	2.09	0.48	2.43	0.51	2.66	0.53
25.0		1.51	0.45	1.79	0.47	2.07	0.49	2.41	0.51	2.64	0.53
27.0		1.48	0.45	1.76	0.47	2.04	0.49	2.38	0.52	2.61	0.53

3D086725

Symbols

- A Air flow rate [m³/min]
- B Bypass factor
- C Wet-bulb temperature [°C WB]
- D Dry-bulb temperature [°C DB]
- E Total capacity [kW]
- F Sensible heat capacity [kW]
- G Power input [kW]

Notes

1. These figures assume the following operation conditions
 - (1) Corresponding refrigerant piping length: 5 m
 - (2) Height difference between outdoor unit and indoor unit: 0 m
2. Nominal capacity and nominal input

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

4

FTXG25LV1BW + RXG25L2V1B FTXG25LV1BS + RXG25L2V1B

A	11
B	11

Cooling 50Hz 220-240V

Indoor		Outdoor temperature [°C DB]																	
C	D	20			25			30			32			35			40		
°C	°C	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	2.46	2.01	0.40	2.35	1.96	0.44	2.24	1.91	0.48	2.19	1.89	0.49	2.12	1.86	0.51	2.01	1.80	0.55
16.0	22	2.57	1.98	0.40	2.46	1.93	0.44	2.35	1.88	0.48	2.30	1.86	0.49	2.23	1.83	0.52	2.12	1.78	0.55
18.0	25	2.68	2.10	0.40	2.57	2.05	0.44	2.46	2.01	0.48	2.41	1.99	0.50	2.34	1.96	0.52	2.23	1.92	0.56
19.0	27	2.74	2.24	0.40	2.62	2.20	0.44	2.51	2.15	0.48	2.47	2.13	0.50	2.40	2.11	0.52	2.29	2.07	0.56
22.0	30	2.90	2.17	0.41	2.79	2.13	0.45	2.68	2.09	0.49	2.63	2.08	0.50	2.57	2.05	0.52	2.45	2.02	0.56
24.0	32	3.01	2.12	0.41	2.90	2.09	0.45	2.79	2.05	0.49	2.74	2.04	0.50	2.68	2.02	0.53	2.56	1.98	0.56

A	11
---	----

Heating 50Hz 220-240V

Indoor		Outdoor temperature [°C WB]									
D		-10		-5		0		6		10	
°C		E	G	E	G	E	G	E	G	E	G
15.0		2.29	0.65	2.67	0.68	3.06	0.71	3.52	0.75	3.82	0.78
20.0		2.17	0.67	2.56	0.70	2.94	0.73	3.40	0.77	3.71	0.80
22.0		2.12	0.68	2.51	0.71	2.89	0.74	3.35	0.78	3.66	0.80
24.0		2.08	0.68	2.46	0.71	2.85	0.75	3.31	0.78	3.61	0.81
25.0		2.05	0.69	2.44	0.72	2.82	0.75	3.28	0.79	3.59	0.81
27.0		2.01	0.69	2.39	0.72	2.77	0.76	3.24	0.79	3.54	0.82

3D086722

Symbols

- A Air flow rate [m³/min]
- B Bypass factor
- C Wet-bulb temperature [°C WB]
- D Dry-bulb temperature [°C DB]
- E Total capacity [kW]
- F Sensible heat capacity [kW]
- G Power input [kW]

Notes

1. These figures assume the following operation conditions
 - (1) Corresponding refrigerant piping length: 5 m
 - (2) Height difference between outdoor unit and indoor unit: 0 m
2. Nominal capacity and nominal input

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

FTXG35LV1BW + RXG35L2V1B

FTXG35LV1BS + RXG35L2V1B

A	10.9
B	0.14

Cooling 50Hz 220-240V

Indoor		Outdoor temperature [°C DB]																	
C	D	20			25			30			32			35			40		
°C	°C	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	3.59	2.71	0.68	3.42	2.63	0.74	3.26	2.55	0.81	3.19	2.52	0.83	3.10	2.47	0.87	2.93	2.39	0.94
16.0	22	3.75	2.66	0.68	3.58	2.59	0.74	3.42	2.51	0.81	3.36	2.48	0.84	3.26	2.44	0.87	3.10	2.37	0.94
18.0	25	3.91	2.80	0.68	3.75	2.73	0.75	3.58	2.66	0.81	3.52	2.63	0.84	3.42	2.59	0.88	3.26	2.52	0.94
19.0	27	3.99	2.96	0.68	3.83	2.89	0.75	3.66	2.82	0.81	3.60	2.79	0.84	3.50	2.76	0.88	3.34	2.69	0.95
22.0	30	4.23	2.85	0.69	4.07	2.79	0.76	3.90	2.73	0.82	3.84	2.71	0.85	3.74	2.68	0.89	3.58	2.62	0.95
24.0	32	4.39	2.78	0.69	4.23	2.73	0.76	4.07	2.67	0.82	4.00	2.65	0.85	3.90	2.62	0.89	3.74	2.57	0.95

A	12.4
---	------

Heating 50Hz 220-240V

Indoor		Outdoor temperature [°C WB]									
D		-10		-5		0		6		10	
°C		E	G	E	G	E	G	E	G	E	G
15.0		2.69	0.83	3.14	0.87	3.60	0.91	4.14	0.96	4.50	0.99
20.0		2.55	0.85	3.01	0.89	3.46	0.93	4.00	0.98	4.36	1.01
22.0		2.50	0.86	2.95	0.90	3.40	0.94	3.94	0.99	4.31	1.02
24.0		2.44	0.87	2.90	0.91	3.35	0.95	3.89	1.00	4.25	1.03
25.0		2.42	0.87	2.87	0.91	3.32	0.95	3.86	1.00	4.22	1.03
27.0		2.36	0.88	2.81	0.92	3.26	0.96	3.81	1.01	4.17	1.04

3D086724

Symbols

- A Air flow rate [m³/min]
- B Bypass factor
- C Wet-bulb temperature [°C WB]
- D Dry-bulb temperature [°C DB]
- E Total capacity [kW]
- F Sensible heat capacity [kW]
- G Power input [kW]

Notes

1. These figures assume the following operation conditions
 - (1) Corresponding refrigerant piping length: 5 m
 - (2) Height difference between outdoor unit and indoor unit: 0 m
2.

--

 Nominal capacity and nominal input

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

4

FTXG50LV1BW + RXG50L2V1B FTXG50LV1BS + RXG50L2V1B

A	10.9
B	0.17

Cooling 50Hz 220-240V

Indoor		Outdoor temperature [°C DB]																	
C	D	20			25			30			32			35			40		
		E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	3.71	2.74	0.95	3.71	2.74	1.08	3.71	2.74	1.20	3.71	2.74	1.25	3.71	2.74	1.33	3.71	2.74	1.44
16.0	22	4.72	3.11	1.02	4.72	3.11	1.14	4.69	3.09	1.25	4.60	3.05	1.29	4.47	2.98	1.35	4.24	2.87	1.45
18.0	25	5.36	3.43	1.06	5.14	3.32	1.16	4.91	3.22	1.26	4.82	3.17	1.30	4.69	3.11	1.36	4.47	3.01	1.46
19.0	27	5.47	3.57	1.06	5.25	3.47	1.16	5.02	3.37	1.26	4.93	3.33	1.30	4.80	3.26	1.36	4.58	3.17	1.46
22.0	30	5.80	3.43	1.07	5.58	3.34	1.17	5.36	3.25	1.27	5.27	3.21	1.31	5.13	3.16	1.37	4.91	3.07	1.47
24.0	32	6.02	3.33	1.07	5.80	3.24	1.17	5.58	3.16	1.27	5.49	3.12	1.31	5.35	3.07	1.38	5.13	2.99	1.48

A	12.6
---	------

Heating 50Hz 220-240V

Indoor		Outdoor temperature [°C WB]									
D	°C	-10		-5		0		5		10	
		E	G	E	G	E	G	E	G	E	G
15.0	3.90	1.34	4.56	1.41	5.21	1.48	6.00	1.55	6.52	1.61	
20.0	3.70	1.38	4.36	1.45	5.01	1.51	5.80	1.59	6.32	1.64	
22.0	3.62	1.39	4.28	1.46	4.93	1.53	5.72	1.60	6.24	1.66	
24.0	3.54	1.41	4.20	1.47	4.85	1.54	5.64	1.62	6.16	1.67	
25.0	3.50	1.42	4.16	1.48	4.81	1.55	5.60	1.63	6.12	1.68	
27.0	3.42	1.43	4.08	1.50	4.73	1.56	5.52	1.64	6.04	1.69	

Symbols

- A Air flow rate [m³/min]
- B Bypass factor
- C Wet-bulb temperature [°C WB]
- D Dry-bulb temperature [°C DB]
- E Total capacity [kW]
- F Sensible heat capacity [kW]
- G Power input [kW]

3D086723

Notes

1. The ratings shown are net capacities which include a deduction for indoor fan motor heat.
2. □ Nominal capacity and nominal input
3. The total capacity, power input and sensible heat capacity must be calculated by interpolation, using the figures in the table (figures not in the table may not be used in the calculation).
4. In case the sensible heat capacity is not mentioned in the table, please calculate it using an approximation between two values in direct proportion.
5. These figures assume the following operation conditions
 - (1) Corresponding refrigerant piping length: 5 m
 - (2) Height difference between outdoor unit and indoor unit: 0 m
6. The air flow rate and bypass factor are mentioned in the table.

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

FVXG25K2V1B + RXG25L2V1B

Cooling 50Hz 220-240V

A	8.9
B	0.1

Indoor		Outdoor temp. (°CDB)																	
C	D	20			25			30			32			35			40		
(°C)	(°C)	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	2.56	2.07	0.41	2.44	2.02	0.45	2.33	1.96	0.49	2.28	1.94	0.51	2.21	1.91	0.53	2.10	1.85	0.57
16.0	22	2.68	2.04	0.42	2.56	1.98	0.46	2.44	1.93	0.50	2.40	1.91	0.51	2.33	1.88	0.54	2.21	1.83	0.58
18.0	25	2.79	2.16	0.42	2.68	2.11	0.46	2.56	2.06	0.50	2.51	2.04	0.51	2.44	2.01	0.54	2.33	1.97	0.58
19.0	27	2.85	2.30	0.42	2.73	2.25	0.46	2.62	2.21	0.50	2.57	2.19	0.52	2.50	2.16	0.54	2.38	2.12	0.58
22.0	30	3.02	2.22	0.42	2.91	2.18	0.46	2.79	2.14	0.50	2.74	2.13	0.52	2.67	2.10	0.54	2.56	2.06	0.58
24.0	32	3.14	2.17	0.43	3.02	2.14	0.47	2.90	2.10	0.51	2.86	2.09	0.52	2.79	2.06	0.55	2.67	2.03	0.59

Heating 50Hz 220-240V

A	9.9
---	-----

Indoor		Outdoor temp. (°CWB)									
D		-10		-5		0		6		10	
(°C)		E	G	E	G	E	G	E	G	E	G
15.0		2.29	0.65	2.67	0.68	3.06	0.71	3.52	0.75	3.82	0.78
20.0		2.17	0.67	2.56	0.70	2.94	0.73	3.40	0.77	3.71	0.80
22.0		2.12	0.68	2.51	0.71	2.89	0.74	3.35	0.78	3.66	0.80
24.0		2.08	0.68	2.46	0.71	2.85	0.75	3.31	0.78	3.61	0.81
25.0		2.05	0.69	2.44	0.72	2.82	0.75	3.28	0.79	3.59	0.81
27.0		2.01	0.69	2.39	0.72	2.77	0.76	3.24	0.79	3.54	0.82

3D087613

SYMBOLS

A:	Air flow rate	(m ³ /min)
B:	Bypass factor	
C:	Wet-bulb temperature	(°CWB)
D:	Dry-bulb temperature	(°CDB)
E:	Total capacity	(kW)
F:	Sensible heat capacity	(kW)
G:	Power input	(kW)

NOTES

- These figures assume the following operating conditions:
 (1) Corresponding refrigerant piping length: 5m
 (2) Height difference between outdoor unit and indoor unit: 0m
- Nominal capacity and nominal input

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

4

FVXG35K2V1B + RXG35L2V1B

Cooling 50Hz 220-240V

A	9.1
B	0.13

Indoor		Outdoor temp. (°CDB)																	
C (°C)	D (°C)	20			25			30			32			35			40		
		E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	3.25	2.40	0.68	3.25	2.40	0.77	3.25	2.40	0.86	3.19	2.37	0.89	3.10	2.32	0.93	2.93	2.24	1.00
16.0	22	3.75	2.53	0.73	2.58	2.45	0.79	3.42	2.37	0.86	3.36	2.34	0.89	3.26	2.29	0.93	3.10	2.22	1.00
18.0	25	3.91	2.63	0.73	2.75	2.56	0.80	3.58	2.49	0.87	3.52	2.46	0.90	3.42	2.41	0.94	3.26	2.34	1.01
19.0	27	3.99	2.76	0.73	3.83	2.69	0.80	3.66	2.62	0.87	3.60	2.59	0.90	3.50	2.55	0.94	3.34	2.48	1.01
22.0	30	4.23	2.66	0.74	4.07	2.60	0.81	3.90	2.53	0.88	3.84	2.51	0.90	3.74	2.47	0.95	3.58	2.41	1.02
24.0	32	4.39	2.58	0.74	4.23	2.53	0.81	4.07	2.47	0.88	4.00	2.45	0.91	3.90	2.41	0.95	3.74	2.36	1.02

Heating 50Hz 220-240V

A	10.2
---	------

Indoor		Outdoor temp. (°CWB)									
D (°C)	E	-10		-5		0		6		10	
		G	E	G	E	G	E	G	E	G	
15.0	3.03	1.01	3.54	1.06	4.05	1.11	4.66	1.17	5.06	1.21	
20.0	2.87	1.04	3.38	1.09	3.89	1.14	4.50	1.20	4.91	1.24	
22.0	2.81	1.06	3.32	1.10	3.83	1.15	4.44	1.21	4.84	1.25	
24.0	2.75	1.06	3.26	1.11	3.77	1.16	4.38	1.22	4.78	1.26	
25.0	2.72	1.07	3.23	1.12	3.73	1.17	4.34	1.23	4.75	1.27	
27.0	2.66	1.08	3.16	1.13	3.67	1.18	4.28	1.24	4.69	1.28	

3D087614

SYMBOLS

A:	Air flow rate	(m ³ /min)
B:	Bypass factor	
C:	Wet-bulb temperature	(°CWB)
D:	Dry-bulb temperature	(°CDB)
E:	Total capacity	(kW)
F:	Sensible heat capacity	(kW)
G:	Power input	(kW)

NOTES

- These figures assume the following operating conditions:
 - Corresponding refrigerant piping length: 5m
 - Height difference between outdoor unit and indoor unit: 0m
- | |
|--|
| |
|--|

 Nominal capacity and nominal input

4 Capacity tables

4 - 1 Cooling/Heating Capacity Tables

FVXG50K2V1B + RXG50L2V1B

Cooling 50Hz 220-240V

A	10.6
B	0.13

Indoor		Outdoor temp. (°CDB)																	
C	D	20			25			30			32			35			40		
(°C)	(°C)	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G	E	F	G
14.0	20	3.79	2.80	1.07	3.79	2.80	1.22	3.79	2.80	1.36	3.79	2.80	1.41	3.79	2.80	1.49	3.79	2.80	1.60
16.0	22	4.81	3.17	1.14	4.81	3.17	1.26	4.81	3.17	1.39	4.79	3.16	1.43	4.65	3.09	1.50	4.42	2.97	1.61
18.0	25	5.58	3.56	1.17	5.35	3.44	1.28	5.12	3.33	1.40	5.02	3.29	1.44	4.88	3.22	1.51	4.65	3.11	1.62
19.0	27	5.70	3.70	1.18	5.47	3.59	1.29	5.23	3.48	1.40	5.14	3.44	1.44	5.00	3.38	1.51	4.77	3.27	1.62
22.0	30	6.04	3.55	1.19	5.81	3.45	1.30	5.58	3.36	1.41	5.49	3.32	1.45	5.35	3.26	1.52	5.11	3.17	1.63
24.0	32	6.27	3.44	1.19	6.04	3.35	1.30	5.81	3.26	1.42	5.72	3.23	1.46	5.58	3.18	1.53	5.34	3.09	1.64

Heating 50Hz 220-240V

A	12.2
---	------


Indoor		Outdoor temp. (°CWB)									
D		-10		-5		0		6		10	
(°C)		E	G	E	G	E	G	E	G	E	G
15.0		3.90	1.33	4.56	1.39	5.21	1.46	6.00	1.53	6.52	1.59
20.0		3.70	1.36	4.36	1.43	5.01	1.49	5.80	1.57	6.32	1.62
22.0		3.62	1.38	4.28	1.44	4.93	1.51	5.72	1.58	6.24	1.64
24.0		3.54	1.39	4.20	1.46	4.85	1.52	5.64	1.60	6.16	1.65
25.0		3.50	1.40	4.16	1.46	4.81	1.53	5.60	1.61	6.12	1.66
27.0		3.42	1.41	4.08	1.48	4.73	1.54	5.52	1.62	5.86	1.66

3D087615

SYMBOLS

A:	Air flow rate	(m ³ /min)
B:	Bypass factor	
C:	Wet-bulb temperature	(°CWB)
D:	Dry-bulb temperature	(°CDB)
E:	Total capacity	(kW)
F:	Sensible heat capacity	(kW)
G:	Power input	(kW)



NOTES

- These figures assume the following operating conditions:
 (1) Corresponding refrigerant piping length: 5m
 (2) Height difference between outdoor unit and indoor unit: 0m
-  Nominal capacity and nominal input

5 Dimensional drawings



5 - 1 Dimensional Drawings

5





6 Centre of gravity

6 - 1 Centre of Gravity



8 Wiring diagrams



8 - 1 Wiring Diagrams - Single Phase



9 Sound data

9 - 1 Sound Pressure Spectrum

RXG20L



Legend


dBA = A-weighted sound pressure level (A scale according to IEC).

A Scale

B High-tap

Low-tap

Location of microphone



The operation noise measuring method is in accordance with JISC9612.

Measuring location: anechoic chamber

Cooling		Total dB	
A	B		
dBA	46		

Background noise already taken into account.

Operating conditions: power source 220-240 V/220 V 50/60 Hz; JIS standard

Heating		Total dB	
A	B		
dBA	47		

Background noise already taken into account.



Operating conditions: power source 220-240 V/220 V 50/60 Hz; JIS standard

Notes

Operating noise varies depending on operation and ambient conditions.

3D086899

RXG25L



Legend


dBA = A-weighted sound pressure level (A scale according to IEC).

A Scale

B High-tap

Low-tap

Location of microphone



The operation noise measuring method is in accordance with JISC9612.

Measuring location: anechoic chamber

Cooling		Total dB	
A	B		
dBA	46		

Background noise already taken into account.

Operating conditions: power source 220-240 V/220 V 50/60 Hz; JIS standard

Heating		Total dB	
A	B		
dBA	47		

Background noise already taken into account.

Operating conditions: power source 220-240 V/220 V 50/60 Hz; JIS standard



Notes

Operating noise varies depending on operation and ambient conditions.

3D086900

9 Sound data

9 - 1 Sound Pressure Spectrum




10 Operation range

10 - 1 Operation Range


10

RXG-L

Cooling mode



Heating mode



Notes

- These figures assume the following operation conditions
 - Equivalent piping length [m] 5.0
 - Height difference between outdoor unit and indoor unit: 0
 - Air flow rate High

3D086777



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check on-going validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

BARCODE

Daikin products are distributed by: