



# FAQ-B / REQ-B

## Wall Mounted Unit



BRC1D52



BRC7E618/510




FAQ71B



REQ71B

- **Wired remote controller** provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible.
- **Home Leave operation:** in case of extended absence, this function helps to save energy and protects from frost. The function automatically keeps the room temperature at a specified favourite comfort level by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- **User Access:** different levels of user access can be selected.
- Ideal for shops, restaurants or offices requiring maximum floor space for furniture, decorations and fittings
- Auto-swing function ensures efficient air distribution via louvers that close automatically when the unit is switched off
- Automatic movable louver can be fixed at any desired angle
- All maintenance operations can be carried out from the front of the unit
- Suitable for Twin, Triple and Double Twin applications



## HEAT PUMP

## NON-INVERTER

Indoor Units				FAQ71BVV1B	FAQ100BVV1B	
Capacity	Cooling capacity	Standard	kW	-	-	
	Heating capacity	Standard	kW	-	-	
Annual energy consumption			kWh	-	-	
EER / COP	Cooling / Heating			-	-	
Energy Label	cooling / heating			-	-	
Dimensions	(Height x Width x Depth)		mm	290x1050x230	360x1570x200	
Weight				kg	13.0	26.0
Air Flow Rate	Cooling	High/Low	m³/min	19.0 / 15.0	23.0 / 19.0	
	Heating	High/Low	m³/min	19.0 / 15.0	23.0 / 19.0	
Sound Power	Cooling	High/Low	dBA	59.0 / 53.0	61.0 / 57.0	
Sound Pressure	Cooling	High/Low	dBA	43.0 / 37.0	45.0 / 41.0	
	Heating	High/Low	dBA	43.0 / 37.0	45.0 / 41.0	
Refrigerant				Type	R-410A	
Power Supply				1~220-240V/50Hz		

Outdoor Unit				REQ71B8V3B	REQ71B8W1B	REQ100B8V3B	REQ100B8W1B
Dimensions		(Height x Width x Depth)		770x900x320		1170x900x320	
Weight				83		102	100
Operation Range	Cooling	Min~Max	°CDB	10.0~46.0			
	Heating	Min~Max	°CWB	-10~15			
Sound Level (nominal)	Sound Power	Cooling	dBA	65.0		70.0	
	Sound Pressure	Cooling	dBA	53.0		57.0	
Refrigerant			Type	R-410A			
Power Supply				1~/230V/50Hz	3N~/400V/50Hz	1~/230V/50Hz	3N~/400V/50Hz
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26			
Piping Length (Maximum)			m	50			
Max Installation Height Difference			m	30			