

Wall Mounted Unit

Seasonal Inverter

FAQ / RZQ-D(B9W1)



BRC1D52
Wired remote
control (standard)



BRC1E51A
Wired remote
control (optional)



Wireless remote
control (optional)



These popular indoor units can be mounted on virtually any type of wall, leaving space free for furniture, decoration and fittings. Wall mounted units are very quiet in operation. An automatic air flow director ensures uniform air flow and temperature distribution by moving the air discharge horizontally and/or vertically.

- **RZQ Seasonal Inverter technology:** first light commercial range in the market optimised for Seasonal Efficiency. Takes account of multiple cooling/heating temperatures as well as unit operation at partial load instead of just full capacity. Will also consider the power consumed by equipment in auxiliary mode (thermostat off, standby mode, OFF mode).
- **Application flexibility:** Comms, computer and server room cooling possible. Also suitable for use in R-22 replacement projects.
- **Wired remote controller:** provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible (BRC1D52 standard / BRC1E51A optional).
- **BRC1E51A – New optional wired controller:** allows easy navigation through menu items, via a personalised display and minimal number of buttons.
- **Home Leave operation:** in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air. It can easily be removed and washed.
- **Fan speed:** 2 fan speeds can be selected, high or low.
- **Easy clean:** Horizontal flaps and front panel can easily be removed and cleaned.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

Height	290mm
Width	1050mm
Depth	230mm



FAQ71B

Height	770mm
Width	900mm
Depth	320mm



RZQ71D

See tables overleaf for full list of dimensions

ENERGY LABEL:
UP TO CLASS
A

HEAT PUMP

SEASONAL INVERTER

Indoor Units				FAQ71B	FAQ100B	
Capacity	Cooling capacity	Standard	kW	7.1	10	
	Heating capacity	Standard	kW	8.0	11.2	
Nominal	EER / COP	Cooling / Heating		3.11 / 3.43	3.04 / 3.49	
	Annual energy consumption		kWh	1141	1390	
	Energy Label	Cooling / Heating		B / B	A / C	
Seasonal (*)	SEER / SCOP	Cooling / Heating		3.48 / -	2.94 / -	
Dimensions	(Height x Width x Depth)		mm	290x1050x230	360x1570x200	
Weight			kg	13.0	26.0	
Air Flow Rate	Cooling	High/Low	m³/min	19.0 / 15.0	23.0 / 19.0	
	Heating	High/Low	m³/min	19.0 / 15.0	23.0 / 19.0	
Sound Power	Cooling	High/Low	dBA	59.0 / 53.0	61.0 / 57.0	
	Heating	High/Low	dBA	59.0 / 53.0	61.0 / 57.0	
Sound Pressure	Cooling	High/Low	dBA	43.0 / 37.0	45.0 / 41.0	
	Heating	High/Low	dBA	43.0 / 37.0	45.0 / 41.0	
Refrigerant			Type	R-410A		
Power Supply				1~/220-240V/50Hz		
Controller		Wired/Wireless		BRC1D52 (Standard) BRC1E51A (Optional) / BRC7E618 (Optional)	BRC1D52 (Standard) BRC1E51A (Optional) / BRC7C510 (Optional)	
Outdoor Unit				RZQ71D3V1	RZQ100D9V1	RZQ100B9W1
Dimensions	(Height x Width x Depth)		mm	770x900x320	1345x900x320	
Weight			kg	67	108	106
Operation Range	Cooling	Min~Max	°CDB	-15.0~50.0		
	Heating	Min~Max	°CWB	-20.0~15.5		
Sound Power	Cooling		dBA	64	65	
Sound Pressure (Standard)	Cooling		dBA	48	50	
	Heating		dBA	50	52	
Sound Level (Night quiet)	Sound Pressure		dBA	43	45	
Refrigerant			Type	R-410A		
Power Supply				1~/220-240V/50Hz		3N~/400V/50Hz
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26		
Piping Length (Maximum)			m	50	75	
Max. internunit level difference			m	0.5		
Max Installation Height Difference			m	30		

(*) Seasonal efficiencies are calculated based on draft PrEn 14825: 2009 (under inquiry stage). Data are subject to change.

your comfort. our world.



Authorised User No. 02061

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

www.daikin.co.uk

Daikin products are distributed by:

FSC

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin units comply with the European regulations that guarantee the safety of the product.

Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.