









For rooms with no false ceilings nor free floor space



Home leave operation

Infrastructure cooling

Vertical auto swing



 > Flat, stylish front panel blends easily within any interior décor and is easier to clean
> Can easily be installed in both new and

- refurbishment projects
- Reduced energy consumption thanks to specially developed DC fan motor
- The air is comfortably spread up- and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- Maintenance operations can be performed easily from the front of the unit

FAQ-C9 + RZQG-L9V1/(8)Y1, RZQSG-L3/9V1/(8)Y1





Indoor unit FAQ 71C9 100C9 Casing Fresh White Colour Dimensions HeightxWidthxDepth 290x1,050x238 340x1,200x240 Unit mm Sound power level Cooling/Heating dBA 61/61 65/65 Sound pressure Cooling High/Low dBA 45/40 49/41 level High/Low dBA 45/40 49/41 Heating R-410A / -Refrigerant Type/GWP

		Seasonal Smart Combination with Seasonal Smart outdoor units ensure high quality, optimal comfort, flexible installation and highest efficiency values.				Seasonal Classic Combination with Seasonal Classic ensures good value for money for all types of commercial applications.				
Efficiency data		FAQ + RZQG/	71C9 + 71L8Y1	100C9 + 100L8Y1	71C9 + 71L9V1	100C9 + 100L9V1	71C9 + 71L3V1	100C9 + 100L9V1	100C9 + 100L8Y1	
Cooling capacity	Nom.		kW	0.051	0.061	0.051	0.061	6.8	0.061	0.061
Heating capacity	Nom.		kW	0.068	0.061	0.068	0.061	7.5	0.061	0.061
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A	++	A+			
		Pdesign	kW	6.80	9.50	6.80	9.50	6.8	9.50	9.50
		SEER		6.51	6.11	6.51	6.11	5.81	5.61	5.61
		Annual energy consumption	kWh	366	545	366	545	410	593	593
	Heating	Energy label			A	.+	A	A+		
	(Average	Pdesign	kW	6.33	10.20	6.33	10.20	6.33	6.81	6.81
	climate)	SCOP		4.02	4.01	4.02	4.01	3.90	4.01	4.01
		Annual energy consumption	kWh	2,205	3,562	2,205	3,562	2,273	2,378	2,378
Nominal efficiency	EER			3.40	3.62	3.40	3.62	3.21	3.01	3.01
	COP			3.70	3.61	3.70	3.61	3.61	3.41	3.41
	Annual energy consumption kWh			1,000	1,315	1,000	1,315	1,059	1,580	1,580
	Energy label Cooling/Heating				A	/A	A/A	B/B	B/B	
Outdoor unit		RZQG	RZQSG	71L8Y1	100L8Y1	71L9V1	100L9V1	71L3V1	100L9V1	100L8Y1

Outdoor unit			RZQG/	RZQSG	71L8Y1	100L8Y1	71L9V1	100L9V1	71L3V1	100L9V1	100L8Y1	
Dimensions	Unit	HeightxW	/idthxDepth	mm	990x940x320	1,430x940x320	990x940x320	1,430x940x320	770x900x320	990x940x320	990x940x320	
Sound power level	Cooling			dBA	64	66	64	66	65	70	69	
Sound pressure	Cooling	Nom.		dBA	48	50	48	50	49/47	53/-	53	
level	Heating	Nom.		dBA	50	52	50	52	51	57	57	
	Night quiet mode	Level 1		dBA	43	45	43	45	-	49	49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50				-15.0~46			
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5				-15~15.5			
Refrigerant	Type/GWP				R-410A/2,087.5							
	Charge		kg/	TCO,Eq	2.9/6.1	4.0/8.4	2.9/6.1	4.0/8.4	2.75/5.7	2.9/6.1	3N~/50/380-415	
Power supply	Phase/Frequency/Voltage			Hz/V 3N~/50		/380-415 1~/50/2		20-240 1~/50/2		220-240	3N~/50/380-415	
Contains fluorinated or			ding to Eurover	t 2012 for	use outside ELL on	ly (2) Nominal effi	ciency: cooling at	35°/27° nominal lo	ad beating at 7°/2	0° nominal load		

Contains fluorinated greenhouse gases (1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)

