




Large Capacity Concealed Ceiling Unit



FDQ-B / RZQ-C(BW1)



Wired remote control as standard



The concealed ceiling units belong to the most aesthetically pleasing and quietest systems for your climate comfort. Only the suction and discharge grilles visible which provide optimum circulation of the conditioned air and even temperature distribution in large or subdivided areas.

- **Super inverter system:** reduces power consumption by up to 70% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- **Application flexibility:** Comms, computer and server room cooling possible (RZQ125 outdoor unit only).
- **Wired remote controller with weekly timer:** provides a 7-day schedule timer, enabling daily or weekly programming. Up to 5 actions per day possible.
- **Home Leave operation:** in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level, by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air. It can easily be removed and washed.
- **Forced off:** The optional forced off enables the unit to switch off automatically, for example when a window is opened.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

Height	350mm
Width	1400mm
Depth	662mm



FDQ125B

Height	1170mm
Width	900mm
Depth	320mm



RZQ125C

See tables overleaf for full list of dimensions

ENERGY LABEL:
UP TO CLASS
A

HEAT PUMP

SUPER INVERTER

Indoor Units				FDQ125B	FDQ200B	FDQ250B	
Nominal Capacity	Cooling capacity	Standard	kW	12.5	20.0	24.1	
	Heating capacity	Standard	kW	14.0	23.0	26.4	
EER / COP	Cooling / Heating			3.01 / 3.81	3.01 / 3.79	3.21 / 3.41	
Annual energy consumption			kWh	2075	3115	4290	
Energy Label	cooling / heating			B / A	A / B	C / C	
Dimensions	(Height x Width x Depth)		mm	350x1400x662	450x1400x900	450x1400x900	
Weight			kg	59.0	93.0	93.0	
Air Flow Rate	Cooling	Medium	m ³ /min	43.0	69.0	89.0	
	Heating	Medium	m ³ /min	43.0	69.0	89.0	
Sound Power	Cooling	Medium	dBA	75.0	81.0	82.0	
Sound Pressure	Cooling	High	dBA	44.0	45.0	47.0	
	Heating	Low	dBA	44.0	45.0	47.0	
Refrigerant			Type	R-410A			
Power Supply				1~/230V/50Hz			
Controller				BRC1D52			
Outdoor Unit				RZQ125CV1	RZQ125BW1	RZQ200C	RZQ250C
Dimensions	(Height x Width x Depth)		mm	1170x900x320	1345x900x320	1680x930x765	1680x930x765
Weight			kg	103	106	183	184
Sound pressure level	Cooling (Night quiet mode)		dBA	50 (45)	50 (45)	57 (-)	57 (-)
	Heating		dBA	52	52	-	-
Sound power level	Cooling		dBA	66	66	78	78
	Heating		dBA	66	66	78	78
Operation Range	Cooling	Min~Max	°CDB	-15.0~50.0	-15.0~50.0	-5.0~46.0	-5.0~46.0
	Heating	Min~Max	°CWB	-20.0~15.5	-20.0~15.5	-15.0~15.0	-15.0~15.0
Refrigerant			Type	R-410A			
Power Supply				1~/220-240V/50Hz	3N~/400V/50Hz	3N~/380-415V/50Hz	
Piping connections	Liquid (OD)/Gas		mm	9.52 / 15.9 / 26		9.5 / 22.2 / -	12.7 / 22.2 / -
Piping Length (Maximum)			m	75		100	
Max Installation Height Difference			m			30	



Authorised User No. 02061

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

www.daikin.co.uk

Daikin products are distributed by:

FSC



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.