




Large Capacity Concealed Ceiling Unit



FDQ-B / RZQS-C



Wired remote control as standard



The concealed ceiling units belong to the most aesthetically pleasing and quietest systems for your climate comfort. Only the suction and discharge grilles visible which provide optimum circulation of the conditioned air and even temperature distribution in large or subdivided areas.

- **Inverter technology:** reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- **Wired remote controller with weekly timer:** provides a 7-day schedule timer, enabling daily or weekly programming. Up to 5 actions per day possible.
- **Home Leave operation:** in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level, by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air. It can easily be removed and washed.
- **Forced off:** The optional forced off enables the unit to switch off automatically, for example when a window is opened.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

| | |
|--------|--------|
| Height | 350mm |
| Width | 1400mm |
| Depth | 662mm |



FDQ125B

| | |
|--------|--------|
| Height | 1170mm |
| Width | 900mm |
| Depth | 320mm |



RZQS125C

See tables overleaf for full list of dimensions

ENERGY LABEL:
UP TO CLASS
B

HEAT PUMP

COMFORT INVERTER

| Indoor Units | | | | FDQ125B |
|------------------------------------|----------------------------|----------|--------|------------------|
| Nominal Capacity | Cooling capacity | Standard | kW | 12.5 |
| | Heating capacity | Standard | kW | 14.0 |
| Annual energy consumption | | | kWh | 2225 |
| EER / COP | Cooling / Heating | | | 2.81 / 3.43 |
| Energy Label | cooling / heating | | | C / B |
| Dimensions | (Height x Width x Depth) | | mm | 350x1400x662 |
| Weight | | | kg | 59.0 |
| Air Flow Rate | Cooling | Medium | m³/min | 43.0 |
| | Heating | Medium | m³/min | 43.0 |
| Sound Power | Cooling | Medium | dBA | 75.0 |
| Sound Pressure | Cooling | High | dBA | 44.0 |
| | Heating | Low | dBA | 44.0 |
| Refrigerant | | | Type | R-410A |
| Power Supply | | | | 1~/230V/50Hz |
| Controller | | | | BRC1D52 |
| Outdoor Unit | | | | RZQS125CV1 |
| Dimensions | (Height x Width x Depth) | | mm | 1170x900x320 |
| Weight | | | kg | 103 |
| Sound pressure level | Cooling (Night quiet mode) | | dBA | 51 (49) |
| | Heating | | dBA | 53 |
| Sound power level | Cooling | | dBA | 67 |
| Operation Range | Cooling | Min~Max | °CDB | -5~46 |
| | Heating | Min~Max | °CWB | -15~15.5 |
| Refrigerant | | | Type | R-410A |
| Power Supply | | | | 1~/230V/50Hz |
| Piping connections | Liquid (OD)/Gas | | mm | 9.52 / 15.9 / 26 |
| Piping Length (Maximum) | | | m | 50 |
| Max Installation Height Difference | | | m | 30 |



Authorised User No. 02061

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

www.daikin.co.uk

Daikin products are distributed by:

FSC

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.



Daikin units comply with the European regulations that guarantee the safety of the product.

Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.