



FLKS-B / RKS-D/B

Flexi type unit



- Can be fitted on either ceiling or lower part of wall (e.g. beneath a window)
- Consumes up to 30% less energy than non-inverter units
- Washable grille
- Achieves set temperature more quickly
- Automatic air flow director ensures uniform air flow and temperature distribution
- Home leave operation saves energy during absence

- Air purification and photocatalytic deodorising filter
- Powerful mode can be selected for rapid cooling
- Indoor unit silent operation
- Outdoor unit silent operation
- Night quiet mode (only in multi application + cooling mode)



COOLING ONLY

INDOOR UNIT (air cooled)		
Cooling capacity	min~nom~max	kW
Nominal input	min~nom~max	kW
EER		
Energy label		
Annual energy consumption	cooling	kWh
Dimensions	HxWxD	mm
Weight		kg
Air flow rate	H/L/SL	m³/min
Sound pressure level	H/L/SL	dB(A)
Sound power level	H	dB(A)
Refrigerant type		
Power supply		
Infrared remote control		VM

INVERTER

FLKS25BVMB	FLKS35BVMB	FLKS50BVMB	FLKS60BVMB	FLKS50BVMB
Cooling capacity	1.3~2.5~3.0	1.4~3.5~3.8	0.90~4.90~5.30	4.90 (nom.)
Nominal input	0.30~0.78~0.96	0.30~1.16~1.27	0.45~1.72~1.95	1.72 (nom.)
EER	3.21	3.02	2.85	2.85
Energy label	A	B	C	C
Annual energy consumption	390	580	860	860
Dimensions	490x1,050x200			
Weight	16			17
Air flow rate	7.6/7*	8.6/7*	11.4/8.5/7.5	12.0/9.3/8.3
Sound pressure level	37/31/28	38/32/29	47/39/36	47/39/36
Sound power level	53	54	63	63
Refrigerant type	R-410A			R-410A
Power supply	1~, 220-240/220-230V, 50/60Hz			1~, 220-240/220-230V, 50/60Hz
Infrared remote control	ARC433A6			ARC433A6

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT			RKS25DVMB	RKS35DVMB	RKS50BVMB9	4MK575,90DVMB	RS50BVMB
Dimensions	HxWxD	mm	550x765x285		735x825x300		735x825x300
Weight		kg	30	32	49		49
Sound pressure level	cooling	H/L	46/43	47/44	47*		47*
Sound power level	cooling	H	61	62	63		63
Operation range	cooling	from~to	-10~46		-10(-15**)-46		-10~46
Refrigerant type			R-410A		R-410A		R-410A
Power supply		VM	1~, 220-240/220-230V, 50/60Hz		1~, 220-240/220-230V, 50/60Hz		1~, 220-240/220-230V, 50/60Hz

* This information was not available at the time of publication.

** Possibility to extend the operation range down to -15°C by turning ON the switch on the outdoor unit PCB. In this case, the unit will stop operation at -20°C or lower and will recover when temperature rises again.