



FLXS-B / RXS-D/B

Flexi type unit



- Can be fitted on either ceiling or lower part of wall (e.g. beneath a window)
- Consumes up to 30% less energy than non-inverter units
- Washable grille
- Achieves set temperature more quickly
- Automatic air flow director ensures uniform air flow and temperature distribution
- Home leave operation saves energy during absence

- Air purification and photocatalytic deodorising filter
- Powerful mode can be selected for rapid cooling and/or heating
- Indoor unit silent operation
- Outdoor unit silent operation
- Night quiet mode (only in multi application + cooling mode)



HEAT PUMP

INVERTER

INDOOR UNIT (air cooled)				FLXS25BVM	FLXS35BVM	FLXS50BVM	FLXS60BVM
Cooling capacity	min ~ nom ~ max	kW		13 ~ 25 ~ 3.0	14 ~ 35 ~ 3.8	0.90 ~ 4.90 ~ 5.30	
Heating capacity	min ~ nom ~ max	kW		13 ~ 34 ~ 4.5	14 ~ 40 ~ 5.0	0.90 ~ 6.10 ~ 7.50	
Nominal input	cooling	min ~ nom ~ max	kW	0.30 ~ 0.78 ~ 0.96	0.30 ~ 1.16 ~ 1.27	0.45 ~ 1.72 ~ 1.95	
	heating	min ~ nom ~ max	kW	0.29 ~ 1.00 ~ 1.50	0.31 ~ 1.25 ~ 1.86	0.31 ~ 1.82 ~ 3.54	
EER	cooling			3.21	3.02	2.85	
COP	heating			3.40	3.20	3.35	
Energy label	cooling			A	B	C	
	heating			B	C	C	
Annual energy consumption	cooling		kWh	390	580	860	
Dimensions	HxWxD		mm	490x1050x200			
Weight			kg	16			17
Air flow rate	cooling	H/L	m³/min	76/7*	8.6/7*	11.4/8.5/7.5	12.0/9.3/8.3
	heating	H/L	m³/min	9.2/7*	9.8/7*	12.1/7.5/6.8	12.8/8.4/7.5
Sound pressure level	cooling	H/L	dB(A)	37/31/28	38/32/29	47/39/36	48/41/39
	heating	H/L	dB(A)	37/31/29	39/33/30	46/35/33	47/37/34
Sound power level	cooling/heating	H	dB(A)	53/7*	54/7*	63/7*	64/63
Refrigerant type				R-410A			
Power supply				1 ~, 220-240/220-230V, 50/60Hz			
Infrared remote control			VM	ARC433A5			

- Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT				RXS25DVM	RXS35DVM	RXS50BVM	4MXS68,80DVM / RMXS112,140,160D
Dimensions	HxWxD		mm	550x765x285			735x825x300
Weight			kg	30	32	49	
Sound pressure level	cooling	H/L	dB(A)	46/43	47/44	47/7*	
	heating	H/L	dB(A)	47/44	48/45	48/7*	
Sound power level	cooling/heating	H	dB(A)	61/62	62/63	63	
Operation range	cooling	from ~ to	°CDB	-10 ~ 46			-10 ~ 46
	heating	from ~ to	°CWB	-15 ~ 20			-15 ~ 18
Refrigerant type				R-410A			R-410A
Power supply			VM	1 ~, 220-240/220-230V, 50/60Hz			1 ~, 220-240/220-230V, 50/60Hz

Multi application only.
For more specifications please refer to page 100 and 104 of this catalogue