



Wall Mounted Unit

INVERTER FTK(X)S-F / RK(X)S-F



Wireless remote control (standard)



Wired remote control (optional)



Home Leave operation

These popular indoor units can be mounted on virtually any type of wall, leaving space free for furniture, decoration and fittings. Wall mounted units are very quiet in operation.

- **Inverter technology:** reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, low noise and reliability.
- **Home Leave operation:** in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level, by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- **Movement sensor function:** if the room remains unoccupied for more than 20 minutes, the system automatically switches to the energy efficient mode. When people return into the room again, the system restores the original setting.
- **Night set mode:** prevents any sudden change in room temperature by gently raising/lowering the temperature before the system stops, so you can sleep more comfortably.
- **Titanium apatite photocatalytic air purifying filter:** superior adsorption power. Besides mould and odours, it also effectively adsorbs and decomposes bacteria and viruses for effective purification and deodorisation of the air inside the room.
- **Dry programme:** Daikin's special dry programme reduces humidity in the rooms without variations in internal temperature.
- **Quiet operation:** lowers the indoor/outdoor unit noise level by 3dB(A) by changing the frequency and fan speed.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

Height	290mm
Width	1050mm
Depth	238mm



FTXS60F

Height	735mm
Width	825mm
Depth	300mm



RXS60F

See tables overleaf for full list of dimensions

**ENERGY LABEL:
UP TO CLASS
B**

COOLING ONLY

INVERTER

Indoor Units				FTKS60F	FTKS71F
Nominal Capacity	Cooling capacity	Minimum	kW	1.7	2.3
		Standard	kW	6.0	7.1
		Maximum	kW	6.7	8.5
EER	Nominal		3.02	3.02	
Annual energy consumption			kWh	995	1175
Energy Label	cooling		B	B	
Dimensions	(Height x Width x Depth)	mm	290x1050x238	290x1050x238	
Weight		kg	12	12	
Air Flow Rate	Cooling	H/M/L/SL	m³/min	16.2 / 13.6 / 11.4 / 10.2	17.4 / 14.6 / 11.6 / 10.6
Sound Power	Cooling	Medium	dBA	61	62
Sound Pressure	Cooling	H/M/L/SL	dBA	45 / 41 / 36 / 33	46 / 42 / 37 / 34
Refrigerant		Type	R-410A		
Power Supply			1~/220-240V/50Hz		
Controller	Wireless/Wired		ARC433B71 (Standard) / BRC944 (Optional)		
Outdoor Unit				RKS60F	RKS71F
Dimensions	(Height x Width x Depth)	mm	735x825x300	770x900x320	
Weight		kg	47	71	
Sound pressure level		H/SL	dBA	49 / 46	52 / 49
Sound power level		H	dBA	63	66
Operation Range	Cooling	Min~Max	°CDB	-10~46	-10~46
Refrigerant		Type	R-410A		
Power Supply			1~/220-240V/50Hz		
Piping connections	Liquid (OD)/Gas/Drain	mm	6.35 / 12.7 / 18	6.35 / 15.9 / 18	
Piping Length (Maximum)		m	30		
Max Installation Height Difference		m	20		

HEAT PUMP

INVERTER

Indoor Units				FTXS60F	FTXS71F
Nominal Capacity	Cooling capacity	Minimum	kW	1.7	2.3
		Standard	kW	6.0	7.1
		Maximum	kW	6.7	8.5
	Heating capacity	Minimum	kW	1.7	2.3
		Standard	kW	7.0	8.2
		Maximum	kW	8.0	10.2
EER / COP	Cooling / Heating		3.02 / 3.43	3.02 / 3.22	
Annual energy consumption			kWh	995	1175
Energy Label	cooling / heating		B / B	B / C	
Dimensions	(Height x Width x Depth)	mm	290x1050x238	290x1050x238	
Weight		kg	12	12	
Air Flow Rate	Cooling	H/M/L/SL	m³/min	16.2 / 13.6 / 11.4 / 10.2	17.4 / 14.6 / 11.6 / 10.6
	Heating	H/M/L/SL	m³/min	17.4 / 15.1 / 12.7 / 11.4	19.7 / 16.9 / 14.3 / 12.7
Sound Power	Cooling	Medium	dBA	61	62
	Heating	Medium	dBA	60	62
Sound Pressure	Cooling	H/M/L/SL	dBA	45 / 41 / 36 / 33	46 / 42 / 37 / 34
	Heating	H/M/L/SL	dBA	44 / 40 / 35 / 32	46 / 42 / 37 / 34
Refrigerant		Type	R-410A		
Power Supply			1~/220-240V/50Hz		
Controller	Wireless/Wired		ARC433B70 (Standard) / BRC944 (Optional)		
Outdoor Unit				RXS60F	RXS71F
Dimensions	(Height x Width x Depth)	mm	735x825x300	770x900x320	
Weight		kg	48	71	
Sound pressure level	Cooling	H/SL	dBA	49 / 46	52-49
	Heating	H/SL	dBA	49 / 46	52-49
Sound power level	Cooling	H	dBA	63	66
Operation Range	Cooling	Min~Max	°CDB	-10~46	-10~46
	Heating	Min~Max	°CWB	-15~18	-15~18
Refrigerant		Type	R-410A		
Power Supply			1~/220-240V/50Hz		
Piping connections	Liquid (OD)/Gas/Drain	mm	6.35 / 12.7 / 18	6.35 / 15.9 / 18	
Piping Length (Maximum)		m	30		
Max Installation Height Difference		m	20		

www.daikin.co.uk

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

Daikin products are distributed by:

FSC



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.