



# FVXS-B / RXS-D/B

## *Floor standing unit*



- Consumes up to 30% less energy than non-inverter units
- Achieves set temperature more quickly
- Home leave operation saves energy during absence
- Dual air discharge flow for better air distribution
- lightweight and compact
- Easy washable grille
- Can be installed against a wall or recessed

- Air purification and photocatalytic deodorising filter
- Powerful mode can be selected for rapid cooling and/or heating
- Indoor unit silent operation
- Outdoor unit silent operation
- Night quiet mode (only in multi application + cooling mode)



### HEAT PUMP

#### INDOOR UNIT (air cooled)

Cooling capacity	min ~ nom ~ max	kW
Heating capacity	min ~ nom ~ max	kW
Nominal input	cooling	min ~ nom ~ max
	heating	min ~ nom ~ max
EER	cooling	
COP	heating	
Energy label	cooling	A
	heating	A
Annual energy consumption	cooling	kWh
Dimensions	HxWxD	mm
Weight		kg
Air flow rate	cooling	H/LSL
	heating	H/LSL
Sound pressure level	cooling	H/LSL
	heating	H/LSL
Sound power level	cooling	H
Refrigerant type	cooling	dB(A)
Power supply		VM
Infrared remote control		

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient). 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.

3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

### INVERTER

FVXS25BVMB	FVXS35BVMB	FVXS50BVMB
1.3 ~ 2.5 ~ 3.0	14 ~ 3.5 ~ 3.8	0.90 ~ 4.80 ~ 5.30
13 ~ 3.4 ~ 4.5	14 ~ 4.5 ~ 5.0	0.90 ~ 6.00 ~ 7.70
0.30 ~ 0.70 ~ 0.920	0.30 ~ 1.09 ~ 1.25	0.45 ~ 1.70 ~ 2.35
0.29 ~ 0.90 ~ 1.39	0.31 ~ 1.32 ~ 1.88	0.31 ~ 1.87 ~ 2.60
3.57	3.21	2.82
3.78	3.41	3.21
A	A	C
A	B	C
350	545	850
600x650x195		
13		
81.7/*	83.7/*	10.8/7.7/6.7
92.7/*	92.7/*	13.2/9.4/8.3
38/26/23	39/27/24	44/36/33
38/26/23	39/29/36	45/36/33
54	55	56
R-410A		
1~, 220-230/220-240V, 50/60Hz		
ARC433AS		



OUTDOOR UNIT	RXS25DVMB	RXS35DVMB	RXS50BVMB
Dimensions	HxWxD	550x765x285	735x825x300
Weight	kg	30	49
Sound pressure level	cooling H/L dB(A)	46/43	47/44
	heating H/L dB(A)	47/44	48/45
Sound power level	cooling/heating H dB(A)	61/62	62/63
Operation range	cooling from ~ to °CDB	-10 ~ 46	-10 ~ 46
	heating from ~ to °CWB	-15 ~ 20	-15 ~ 18
Refrigerant type		R-410A	R-410A
Power supply	VM	1~, 220-240/220-230V, 50/60Hz	1~, 220-240/220-230V, 50/60Hz

\* This information was not available at the time of publication.