




# MXS-D

Multi model application -  
inverter controlled



2MXS40D



2,3MXS52D/4MXS68D



4MXS80D

## CONNECTABLE INDOOR UNITS

	2MXS40DVB	2MXS52DVB	3MXS52DVB	4MXS68DVB	4MXS80DVB
New wall mounted unit	FTXS20,25,35D	FTXS20,25,35D	FTXS25,25,35D / CTXS50D	FTXS25,25,35D / CTXS50D	FTXS25,25,35D / CTXS50D
Wall mounted unit	FTXS20,25,35C	FTXS20,25,35C/FTXS50B	FTXS20,25,35C/FTXS50B	FTXS20,25,35C/FTXS50,60B	FTXS20,25,35C/FTXS50,60,71B
Floor standing unit		FLXS25,35,50B	FLXS25,35,50B	FLXS25,35,50B	FLXS25,35,50B
Flexi type unit	FLXS25,35B	FLXS25,35B	FLXS25,35,50B	FLXS25,35,50,60B	FLXS25,35,50,60B
Slim concealed ceiling unit	FDXS25,35C	FDXS25,35C/CDXS50C	FDXS25,35C / CDXS50C	FDXS25,35C / CDXS50,60C	FDXS25,35C / CDXS50,60C
4-way blow ceiling mounted cassette (600x600)		FFQ25,35,50B/1B	FFQ25,35,50B	FFQ25,35,50,60B	FFQ25,35,50,60B
4-way blow ceiling mounted cassette (950x950)		FCQ35,50B	FCQ35,50B	FCQ35,50,60B	FCQ35,50,60B
Ceiling suspended cassette		FHQ35,50B	FHQ35,50B	FHQ35,50,60B	FHQ35,50,60B

## HEAT PUMP

NEW

INDOOR UNIT			FTXS20DVMW/L	FTXS25DVMW/L	FTXS35DVMW/L	CTXS50DVMW/L
Dimensions	HxWxD	mm	283x800x195			
Weight		kg	9	9	9	9
Air flow rate	cooling	H/L	13~2.0~2.6	13~2.5~3.0	14~3.4~3.8	
	heating	H/L	13~2.7~4.1	13~3.4~4.5	14~4.0~5.0	
Sound pressure level	cooling	H/LSL	38/25/22	38/25/22	39/26/23	46/35/32
	heating	H/LSL	38/28/25	38/28/25	39/29/26	44/33/30
Sound power level	cooling	H	56	56	57	64
	heating	H	56	56	57	62
Infrared remote control			ARC433A50			

INDOOR UNIT			FTXS20CVMB	FTXS25CVMB	FTXS35CVMB	FTXS50BVB	FTXS60BVB	FTXS71BVB
Dimensions	HxWxD	mm	273x784x195			290x795x238	290x1050x238	
Weight		kg	75			9	12	12
Air flow rate	cooling	H/L	7.7*	7.7*	7.7*	11.4/8.0/7.1	16.2/11.4/10.2	16.7/11.6/10.6
	heating	H/L	7.8*	7.8*	8.1*	12.6/8.9/7.7	17.4/12.7/11.4	18.5/13.5/12.1
Sound pressure level	cooling	H/LSL	38/25/22	38/25/22	39/26/23	44/35/32	45/36/33	46/37/34
	heating	H/LSL	38/28/25	38/28/25	39/29/26	42/22/30	44/35/32	46/37/34
Sound power level	cooling	H	56	56	57	63	63	63
	heating	H	56	56	57	-	-	-
Infrared remote control			ARC433A1			ARC433A21	ARC433A213	

INDOOR UNIT			FLXS25BVB	FLXS35BVB	FLXS50BVB	FLXS60BVB
Dimensions	HxWxD	mm	490x1,050x200			
Weight		kg	16			
Air flow rate (H/L)	cooling	H/L	7.6/6.0/5.2	8.6/6.6/5.6	11.4/8.5/7.5	12.0/9.3/8.3
	heating	H/L	9.2/7.4/6.6	9.8/8.0/7.2	12.1/7.5/6.8	12.8/8.4/7.5
Sound pressure level (H/LSL)	cooling	H/LSL	37/31/28	38/32/29	47/39/36	48/41/39
	heating	H/LSL	37/31/29	39/33/30	46/35/33	47/37/34
Sound power level (H)	cooling	H	53	54	63	64
Infrared remote control			ARC33A5			

INDOOR UNIT			FVXS25BVB	FVXS35BVB	FVXS50BVB
Dimensions	HxWxD	mm	600x650x195		
Weight		kg	13		
Air flow rate	cooling	H/L	8.1/4.3/3.4	8.3/4.3/3.4	10.8/7.7/6.7
	heating	H/L	9.2/4.8/3.5	9.2/5.0/3.6	13.2/9.4/8.3
Sound pressure level	cooling	H/LSL	38/26/23	39/27/24	44/36/33
	heating	H/LSL	38/26/23	39/29/36	45/36/33
Sound power level	cooling	H	54	55	56
Infrared remote control			ARC433A5		

# HEAT PUMP

NEW

NEW

INDOOR UNIT			FDXS25CVMB	FDXS35CVMB	CDXS50CVMB	CDXS60CVMB
Dimensions	HxWxD	mm	200x900x620		200x900x620	200x1100x620
Weight		kg	25		27	30
Air flow rate	cooling	H/L	9.5/8.0/6.7	10.0/8.5/7.0	12.0/10.0/8.4	16.0/13.5/11.2
	heating	H/L	9.5/8.0/6.7	10.0/8.5/7.0	12.0/10.0/8.4	16.0/13.5/11.2
Sound pressure level	cooling	H/L/SL	35/31/29	35/31/29	37/33/31	38/34/32
	heating	H/L/SL	35/31/29	35/31/29	37/33/31	38/34/32
Sound power level	cooling	H	53/53	53/53	55	56
Infrared remote control					ARC433A7	

INDOOR UNIT			FDBQ25B7V1			
Dimensions	HxWxD	mm	230x652x502			
Weight		kg	17			
Air flow rate	cooling	H/L	6.5/5.2			
	heating	H/L	35/28			
Sound pressure level	cooling	H/L	35/29			
	heating	H/L	35/29			
Sound power level	cooling	H	55			
Wired remote control			BRC1D527			

INDOOR UNIT			FBQ35B7V1	FBQ50B7V1	FBQ60B7V1
Dimensions	HxWxD	mm		300x700x800	300x1000x800
Weight		kg	30	31	41
Air flow rate	cooling	H/L	11.5/9	14/10	19/14
	heating	H/L			
Sound pressure level	cooling	H/L		33/29	34/30
	heating	H/L		33/29	34/30
Sound power level	cooling	H	52	53	60
	heating	H	52	53	60
Wired remote control				BRC1D527	
<b>DECORATION PANEL</b>			BYB545DW1		BYB571DW1
Dimensions	HxWxD	decoration panel	mm	55x880x500	55x1100x500
Weight		decoration panel	kg	3.5	4.5

INDOOR UNIT			FCQ35B7V1	FCQ50B7V1	FCQ60B7V1
Dimensions	HxWxD	mm		230x840x840	
Weight		kg	23	23	23
Air flow rate	cooling	H/L	14/10	15/11	18/14
	heating	H/L			
Sound pressure level	cooling	H/L		31/27	33/28
	heating	H/L		31/27	33/28
Sound power level	cooling	H	48		50
	heating	H	48		50
Infrared remote control				BRC7C512W	
Wired remote control				BRC1D527	
<b>DECORATION PANEL</b>			BYC125K7W1B		
Dimensions	HxWxD	decoration panel	mm	40x950x950	
Weight		decoration panel	kg	5	

INDOOR UNIT			FFQ25B7V1B	FFQ35B7V1B	FFQ50B7V1B	FFQ60B7V1B
Dimensions	HxWxD	mm			286x575x575	
Weight		kg	175	175	175	175
Air flow rate	cooling	H/L	9/6.5	10/6.5	12/8	15/10
	heating	H/L	29.5/24.5	32/25	36/27	41/32
Sound pressure level	cooling	H/L	29.5/24.5	32/25	36/27	41/32
	heating	H/L	29.5/24.5	32/25	36/27	41/32
Sound power level	cooling	H	46.5	49	53	58
	heating	H	46.5	49	53	58
Infrared remote control					BRC7E530W7	
Wired remote control					BYFQ60B7W1	
<b>DECORATION PANEL</b>			BRC1D527			
Dimensions	HxWxD	decoration panel	mm	55x700x700		
Weight		decoration panel	kg	2.7		

INDOOR UNIT			FHQ35BUV1	FHQ50BUV1	FHQ60BUV1
Dimensions	HxWxD	mm		195x960x680	195x1160x680
Weight		kg	24	25	27
Air flow rate	cooling	H/L	13/10	13/10	17/13
	heating	H/L			
Sound pressure level	cooling	H/L	37/32	38/33	39/33
	heating	H/L	37/32	38/33	39/33
Sound power level	cooling	H/L	53/48	54/49	55/49
	heating	H/L	53/48	54/49	55/49
Infrared remote control				BRC7E63W	
Wired remote control				BRC1D527	

OUTDOOR UNIT			2MXS40DVMB	2MXS52DVMB	3MXS52DVMB	4MXS68DVMB	4MXS80DVMB
Dimensions	HxWxD	mm	640x685x285		735x936x300		908x900x320
Weight		kg	39	55	55	59	73
Sound pressure level	cooling	H/L	47/43	46/*	46/*	48/*	48/*
	heating	H/L	48/44	47/*	47/*	49/*	49/*
Sound power level	cooling	H	62	59	59	61	61
Operation range	cooling	from ~ to	°CDB	+10 ~ 46		-10 ~ 46	
	heating	from ~ to	°CDB	-10 ~ 15.5		-15 ~ 15.5	
Refrigerant type					R-410A		
Power supply					1 ~, 220-240/220-230V, 50/60Hz		

\* This information was not available at the time of publication.

PRELIMINARY INFORMATION