



Ururu Sarara

The complete solution

FTXZ-N / RXZ-N

The perfect environment

Daikin's Ururu Sarara unit is the most complete air conditioning solution available – it combines industry leading efficiencies with 5 separate air treatments to ensure you always have the perfect environment.

Humidification: A unique built-in humidification element in the outdoor unit absorbs the moisture present in the outside air and sends it to the indoor unit. Since moisture is not absorbed from the room's air, quick and effective humidification is possible, even with the drier air of winter – without the need for a separate water tank.

Dehumidification: During summer, a high degree of ambient air humidity, even at moderate temperatures, can make a room feel hot and oppressive. The Ururu Sarara unit reduces indoor humidity while maintaining an even room temperature. This feature prevents over cooling and creates optimal comfort, even with a lower indoor temperature.

Air purification: The Ururu Sarara purifies the incoming air. The air is purified by passing through dust and pollen filtration before the photocatalytic air purification filter breaks down any odours such as cigarette smoke and cooking smells. In the final stage, the Flash Streamer gives the air a further treatment: it breaks down any possible remnants of formaldehyde, viruses and moulds.

Ventilation: Unlike a conventional air conditioner, the Ururu Sarara brings fresh, conditioned air into the room. The Ururu Sarara is the very first residential heat pump system that – because of its powerful ventilation capacity of 32 m³/h – can fill a room of more than 26 m² with fresh air in less than two hours. Furthermore, the incoming air is brought in at the desired temperature without thermal loss.

Heating & Cooling: Last, but not least, the Ururu Sarara can deliver cooling or heating, at industry leading levels of efficiency.

The Ururu Sarara comes with an infra-red remote controller for simple, effective, programming of all functions. It is also possible to control online from a smart-phone or tablet, using the optional Wi-Fi adaptor.

R-32 **BLUEEVOLUTION**



FTXZ35



RXZ25-50N




BRC073 (optional)



ARC477A1



BRP069A42 (optional)



WI-FI ADAPTOR
AVAILABLE AS AN OPTION



FTXZ-N / RXZ-N

R-32 BLUEEVOLUTION

Features	Benefits
2 area intelligent eye	Directs airflow away from people in the room, for comfort. If room is empty, set-point will adjust by 2°C to ensure room is not excessively heated or cooled when empty
Natural wind air flow	Subtly alters the fan-speed to mimic natural breezes, rather than a constant air speed
Self cleaning filter	The filter is brushed automatically, and any dust collected in a box within the indoor unit. This can be quickly & easily emptied. By keeping the filter clean, running costs can be reduced by approximately 25%

Indoor Units			FTXZ25N	FTXZ35N	FTXZ50N
Capacity	UK Total Cooling	kW	2.79	3.90	5.58
	UK Sensible Cooling	kW	2.39	2.88	3.77
	Nominal Cooling	kW	2.5	3.5	5.0
	Nominal Heating	kW	3.6	5.0	6.3
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+++	A+++	A+++
	Pdesign	kW	2.5	3.5	5.0
	SEER		9.54	9.00	8.60
	Annual Energy Consumption	kWh	92	136	203
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+++	A+++	A+++
	Pdesign	kW	3.5	4.5	5.6
	SCOP		5.90	5.73	5.50
	Annual Energy Consumption	kWh	831	1100	1427
Nominal Efficiency	EER/COP		6.10 / 5.80	5.30 / 5.00	4.55 / 4.47
Air Flow Rate (Cooling)	High / Nom / Low / Silent	m³/sec	0.180 / 0.125 / 0.090 / 0.067	0.200 / 0.140 / 0.090 / 0.067	0.250 / 0.153 / 0.110 / 0.077
Dimensions	Height	mm	295	295	295
	Width	mm	798	798	798
	Depth	mm	372	372	372
Weight		kg	15	15	15
Sound Pressure (Cooling)	High / Nom / Low / Silent	dBA	38 / 33 / 26 / 19	42 / 35 / 27 / 19	47 / 38 / 30 / 23
Sound Pressure (Heating)	High / Nom / Low / Silent	dBA	39 / - / 28 / 19	42 / - / 29 / 19	44 / - / 31 / 24
Sound Power (Cooling)		dBA	54	57	60

Outdoor Units			RXZ25N	RXZ35N	RXZ50N
Dimensions	Height x Width x Depth	mm	693 x 795 x 300		
Weight		kg	50		
Electrical Details	Power Supply		1ph		
	Running Current	A	1.80	2.80	4.80
	Starting Current	A	2.8	4.4	6.2
	Max Fuse Size	A	16	16	16
Interconnection Wiring	Core / Cable size		3+E / 1.5		
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)
Pipework	Maximum Length	m	10	10	10
	Maximum Vertical Rise	m	8	8	8
	Precharged to	m	10	10	10
	Additional charge	g/m	-	-	-
	Holding Charge	kg	1.34	1.34	1.34
Sound Pressure (Cooling)	High / Low / Silent	dBA	46 / - / -	48 / - / -	49 / - / -
Sound Pressure (Heating)	High / Low / Silent	dBA	46 / - / -	48 / - / -	50 / - / -
Sound Power (Cooling)		dBA	59	61	63
Operating Range (Cooling)	Min / Max	°CDB	-10 / 43	-10 / 43	-10 / 43
Operating Range (Heating)	Min / Max	°CWB	-20 / 18	-20 / 18	-20 / 18
Air Flow Rate (Cooling)	High	m³/sec	0.516	0.573	0.673
ECA Eligible			☑	☑	☑

Accessory Ref	Description
BRP069A42	Wi-fi adaptor to connection on on-line controller
KRP413A1S	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A2S	Adaptor PCB for interface to Daikin centralised control systems
KLIC-DD	KNX interface for Split type systems
RTD-RA	Adaptor PCB for Modbus connection and/or extended system functions
KPMH974A42	Hose for humidification (8m length)

Accessory Ref	Description
KPMH974A402	Humidification hose extension set (2m length)
KPMJ942A4	Humidification hose extension joints (10 pieces)
KPMJ983A4L	L-shaped joints for humidification hose (10 pieces)
KPMH950A4L	L-shaped cuffs for humidification hose (10 pieces)
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with K.CWB90-2

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

