




# FXYP


## 2-WAY BLOW CEILING MOUNTED CASSETTE

### Stylish & compact

- Slim unit can be installed in a ceiling void of only 355mm



- Depth of all units is 600mm : easy installation in false ceilings
- Whisper quiet operation: down to 28dBA
- Long life filter is provided as standard



- Drain-up pump with 600mm lift fitted as standard
- Leaves maximum floor and wall space for furniture and decorations
- Auto-swing mechanism ensures even room air and temperature distribution and prevents ceiling soiling.

### Less maintenance

- Maintenance operations can be performed by removing the front panel
- Easy to clean flat suction grille
- Detachable swing flaps



BRC1C517



BRC7C62/67

Easy installation in narrow ceiling voids



## FXYCP - K7V19

Nominal cooling capacity				kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	14.0
Nominal heating capacity				kW	2.5	3.2	4.0	5.0	6.3	8.0	10.0	16.0
Power input	Cooling	W		77	92		130		161	209	256	
	Heating	W		44	59		97		126	176	223	
Power supply					1~, 50Hz, 230V							
Dimensions	Unit	HxWxD	mm	305x780x600				305x995x600		305x1,180x600	305x1,670x600	
	Decoration panel	HxWxD	mm	53x1,030x680				53x1,245x680		53x1,430x680	53x1,920x680	
Weight	Unit	kg		26		31	32	35	47	48		
	Decoration panel	kg		8		8.5		9.5	12			
Casing					galvanised steel plate							
Colour	Decoration panel			white (10Y9/0.5)								
Sound pressure level	High	dB(A)		33	35		35.5		38	40	45	
	Low	dB(A)		28	29		30.5		33	35	39	
Sound power level				dB(A)	45	50		50	52	54	60	
Air flow rate	High	m³/h		420	540		720		990	1,560	1,980	
	Low	m³/h		300	390		540		780	1,260	1,500	
Air filter					resin net with mold resistant							
Temperature control					microprocessor thermostat for cooling and heating							
Piping connections	Liquid	Flare	mm	Ø 6.4				Ø 9.5		Ø 9.5		
	Gas	Flare	mm	Ø 12.7				Ø 15.9		Ø 19.1		
	Drain	mm		VP25, external diameter 32, internal diameter 25								
Sound absorbing thermal insulation					felt / urethane foam							
Safety devices					PC board fuse, fan motor thermal fuse, drain pump fuse							

- Notes:
- Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB  
outdoor temperature: 35°CDB  
equivalent refrigerant piping: 8m (horizontal)
  - Nominal heating capacities are based on: indoor temperature: 20°CDB  
outdoor temperature: 7°CDB, 6°CWB  
equivalent refrigerant piping: 8m (horizontal)
  - Capacities are net, including a deduction for cooling (an addition for heating) for indoor fan motor heat

## ACCESSORIES

### FXYCP - K7V19

Wired remote control		BRC1C517			
Infrared remote control	Cooling only	BRC7C67			
	Heat pump	BRC7C62			
Decoration panel		BYBC32GJW1	BYBC50GJW1	BYBC63GJW1	BYBC125GJW1
High efficiency filter 65% *1		KAFJ532G36	KAFJ532G56	KAFJ532G80	KAFJ532G160
High efficiency filter 90% *1		KAFJ533G36	KAFJ533G56	KAFJ533G80	KAFJ533G160
Filter chamber for bottom suction		KDDFJ53G36	KDDFJ53G56	KDDFJ53G80	KDDFJ53G160
Replacement long life filter		KAFJ531G36	KAFJ531G56	KAFJ531G80	KAFJ531G160

- Note:
- \*1. Filter chamber is required when installing a high efficiency filter