







Whisper quiet



Multi tenant

Slim design for flexible installation

- Compact dimensions, can easily be mounted in a ceiling void of only 240mm
- Medium external static pressure up to 44Pa facilitates unit use with flexible ducts of varying lengths
- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- Auto cleaning filter option ensures maximum efficiency, comfort and reliability by regular filter cleaning
- Multi zoning kit allows multiple individually-controlled climate zones to be served by one indoor unit

FXDQ-A3




Indoor unit			FXDQ	15A3	20A3	25A3	32A3	40A3	50A3	63A3
Cooling capacity	Nom.		kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.	0.071				0.078	0.099	0.110	
	Heating	Nom.	kW	0.068				0.075	0.096	0.107
Required ceiling void > mm				240						
Dimensions	Unit	Height	mm	200						
		Width	mm	750 950					1,150	
		Depth	mm	620						
Weight	Unit		kg	22 26				26	29	
Casing	Colour			Not painted (galvanised)						
	Material			Galvanised steel						
Fan-Air flow rate - 50Hz	Cooling	High/Low	m³/min	7.5/6.4	8.0/6.4		10.5/8.5	12.5/10.0	16.5/13.0	
Fan-External static	High Pa			30				44		
pressure	Nom. Pa			10				15		
Air filter	Type Removable / washable									
Sound power level	Cooling	High/Nom.	dBA	50/-	51/-		52/-	53/-	54/-	
Sound pressure level	Cooling	High/Nom./Low	dBA	32/31/27	33/31/27		34/32/28	35/33/29	36/34/30	
Refrigerant	Туре		R-410A							
	GWP			2,087.5						
Piping connections	Liquid OD mm			6,35						9,52
	Gas	OD	mm	12.7						15.9
	Drain			VP20 (I.D. 20/O.D. 26)						
Power supply	Phase/Freque	ency/Voltage	1~/50/60/220-240/220							
Current - 50Hz	Maximum fuse amps (MFA) A			16						
Control systems	Infrared remote control			BRC4C65 / BRC4C66						
	Wired remote control			BRC1D528 / BRC1E51						
	Simplified wired remote control for hotel applications			-						

Contains fluorinated greenhouse gases





Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



N17-243 08/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.