


FXHQ-M Ceiling suspended unit

FXHQ32M




- Reduced sound pressure level • Leaves maximum floor and wall space .
- for furniture decoration and fittings Can be installed both in new and
- existing buildings Use of W-shaped Coanda flap enhances horizontal and vertical air circulation characteristics
- Wider air discharge thanks to Coanda • effect: up to 100 degrees
- Easy installation and maintenance
- Long life filter fitted as standard
- Drain pump kit available as accessory





w w w . d a i k i n e u r o p e . c o m



FXHQ-MVE				
INDOOR UNIT		32	63	100
Cooling capacity kW		3.6	7.1	11.2
Heating capacity kW		4.0	8.0	12.5
Nominal input co	ioling W	111	115	135
S he	eating W	111	115	135
Dimensions (HxWxD) mm		195x960x680	195x1,160x680	195x1,400x680
Weight D an kg		24	28	33
Air flow rate (H/L) M=4 LUA m ³ /min		12/10	17.5/14	25/19.5
Sound pressure level (H/L)(220V)	dB(A)	36/31	39/34	45/37
Sound power level dB(A)		*	*	*
Refrigerant type		R-410A		
Power supply VE		1 ~, 50Hz, 220-240V		
Infrared remote control cooling heating		BRC7E66		
		BRC7E63W		
Wired remote control		BRCID517		

* Sound power levels were not available at time of publication