



FXLQ20-25P



BRC1E52A/B

BRC4C65



FXLQ-P

Floor Standing Unit

VRV Indoor unit

The floor standing unit can be installed quickly and easily in new or existing facilities in a variety of applications

The Daikin VRV indoor unit range is one of the widest on the market, offering no less than 26 stylish and elegant models in 116 different variants - all designed to maximise comfort, minimise operating noise and simplify installation and servicing.

Designed to fit rooms of any size and shape, Daikin indoor units are also user friendly, ultra reliable, easy to control and quiet in operation.

From January 2013, all indoor units will have to comply with the Ecodesign legislation on fans. As a market leader, Daikin has ensured that all indoors units comply with this legislation by adopting DC fans in all indoor units, improving their energy efficiency even further.

Features and Benefits

- › Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011)
- › Unit can be installed as a free standing model, using an optional back plate
- › Its low height means the unit fits perfectly beneath a window
- › Requires very little installation space
- › Wired remote control can easily be integrated in the unit
- › Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate



INDOOR UNIT				FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
Cooling capacity	Nom.		kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	2.5	3.2	4.0	5.0	6.3	8.000
Power input - 50Hz	Cooling	Nom.	kW	0.049		0.090		0.110	
	Heating	Nom.	kW	0.049		0.090		0.110	
Casing Colour				Fresh white (RAL9010) / Dark grey (RAL7011)					
Dimensions	Unit	HeightxWidthxDepth	mm	600x1,000x232		600x1,140x232		600x1,420x232	
Weight	Unit		kg	27		32		38	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m³/min	7/6		8/6	11/8.5	14/11	16/12
Sound power level	Cooling	Nom.	dBA	-					
Sound pressure level	Cooling	High/Low	dBA	35/32			38/33	39/34	40/35
Refrigerant	Type			R-410A					
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/					9.52/15.9/
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)		A	15					

See databook for option details.

In all of us,
a green heart



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.

FSC logo



Daikin products are distributed by: