



FXNQ20-32P



BRC1E52A/B BRC4C65

- › Its low height enables the unit to fit perfectly beneath a window
- › Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- › Requires very little installation space
- › The connecting port faces downward, eliminating the need to attach auxiliary piping



INDOOR UNIT				FXNQ20P	FXNQ25P	FXNQ32P	FXNQ40P	FXNQ50P	FXNQ63P
Cooling capacity	Nom.		kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.	kW	0.049		0.090		0.110	
	Heating	Nom.	kW	0.049		0.090		0.110	
Dimensions	Unit	HeightxWidthxDepth	mm	610x930x220		610x1,070x220		610x1,350x220	
Weight	Unit		kg	19		23		27	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min	7/6		8/6	11/8.5	14/11	16/12
Sound power level	Cooling	Nom.	dBA	-					
Sound pressure level	Cooling	High/Low	dBA	35/32			38/33	39/34	40/35
Refrigerant	Type			R-410A					
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/					9.52/15.9/
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)		A	15					