



# RWEYQ-MY1

## Water-cooled VRV



RWEYQ10M

- Wide condensing unit range: 10, 20 & 30HP via 1 single refrigerant circuit
- High COP values: 5.21 nominal value
- Up to 32 indoor units connectable to a 30HP condensing unit
- Wide range of indoor units: 13 different models in a total of 75 variations
- Compact design
- Operation range (inlet water temperature): 10-45°C
- Connectable to current Daikin control systems: DS-net, Intelligent Touch Controller, Intelligent Manager, BACnet Gateway, DMS-IF
- Flexible piping length

### HEAT RECOVERY

Outdoor Unit				RWEYQ10MY1	RWEYQ20MY1	RWEYQ30MY1
Capacity range		HP	10	20	30	
Capacity	Cooling	kw	26.70	53.40	80.10	
	Heating	kw	31.50	63.00	94.50	
Power input (Nominal)	Cooling	kw	6.03	12.10	18.10	
	Heating	kw	6.05	12.10	18.20	
Dimensions	(Height x Width x Depth)		1000x780x550			
Weight		kg	150	300	450	
Sound Level	Sound Pressure	Cooling	dBA	51.0	54.0	56.0
Refrigerant	R-410A					
Power Supply	3~/380-415V/50Hz					
Max n° of indoor units to be connected			16	20	32	
Piping connections	Liquid (OD)/Discharge Gas	mm	9.5 / 22.2 / 19.1	15.9 / 28.6 / 22.2	19.1 / 34.9 / 28.6	

### HEAT PUMP

Outdoor Unit				RWEYQ10MY1	RWEYQ20MY1	RWEYQ30MY1
Capacity range		HP	10	20	30	
Capacity	Cooling	kw	26.70	53.40	80.10	
	Heating	kw	31.50	63.00	94.50	
Power input (Nominal)	Cooling	kw	6.03	12.10	18.10	
	Heating	kw	6.05	12.10	18.20	
Dimensions	(Height x Width x Depth)		1000x780x550			
Weight		kg	150	300	450	
Sound Level	Sound Pressure	Cooling	dBA	51.0	54.0	56.0
Refrigerant	R-410A					
Power Supply	3~/380-415V/50Hz					
Max n° of indoor units to be connected			16	20	32	
Piping connections	Liquid (OD)/Discharge Gas	mm	9.5/22.2	15.9/28.6	19.1/34.9	