



# RXYSQ4-6PA7V(Y)1B

## VRV<sup>®</sup>III-S Inverter Heat Pump



RXYSQ4-5-6PA7V(Y)1B

- High COP values
- Easy installation thanks to automatic refrigerant charging operation, automatic test operation
- Super wide range of indoor units
- Power consumption limit setting
- Small capacities - 4, 5 & 6HP
- Slim & flexible design
- Space saving outdoor unit

### HEAT PUMP

Outdoor Unit				RXYSQ4PA7Y1B	RXYSQ5PA7Y1B	RXYSQ6PA7Y1B
Capacity range		HP	4	5	6	
Capacity	Cooling	kw	11.2	14.0	15.5	
	Heating	kw	12.5	16.0	18.0	
Dimensions	(Height x Width x Depth)		mm 1,345x900x320			
Weight			kg 120			
Sound Level	Sound Power	Cooling	dBA 66	67	69	
		Heating	dBA 52	53	55	
	Sound Pressure	Cooling	dBA 50	51	53	
Operation Range	Cooling	Min~Max	°CDB -5~46			
		Heating	Min~Max	°CWB -20~-15.5		
Refrigerant			R-410A			
Power Supply			1N~/220-240V/50Hz			
Max n° of indoor units to be connected			6	8	9	
Piping connections	Liquid (OD)/Gas/Drain	mm	9.52 / 15.9 / 26 x 3			
Max total length			m 300			

### HEAT PUMP

Outdoor Unit				RXYSQ4PA7Y1B	RXYSQ5PA7Y1B	RXYSQ6PA7Y1B
Capacity range		HP	4	5	6	
Capacity	Cooling	kw	11.2	14.0	15.5	
	Heating	kw	12.5	16.0	18.0	
Dimensions	(Height x Width x Depth)		mm 1,345x900x320			
Weight			kg 120			
Sound Level	Sound Power	Cooling	dBA 66	67	69	
		Heating	dBA 52	53	55	
	Sound Pressure	Cooling	dBA 50	51	53	
Operation Range	Cooling	Min~Max	°CDB -5~46			
		Heating	Min~Max	°CWB -20~-15.5		
Refrigerant			R-410A			
Power Supply			3N~/380-415V/50Hz			
Max n° of indoor units to be connected			6	8	9	
Piping connections	Liquid (OD)/Gas/Drain	mm	9.52 / 15.9 / 26 x 3			
Max total length			m 300			