



RXYSQ-P8

VRV®III-S inverter heat pump



RXYSQ4-5-6PA7V(Y)1B

- High COP values
- Easy installation thanks to automatic refrigerant charging operation, automatic test operation
- Wide range of indoor units
- Power consumption limit setting
- Small capacities - 4, 5 & 6HP
- Slim & flexible design
- Space saving outdoor unit

HEAT PUMP				RXYSQ4P8V1	RXYSQ5P8V1	RXYSQ6P8V1
Outdoor Unit (Single Phase)						
Capacity range			HP	4	5	6
Capacity	Cooling		kW	11.2	14.0	15.5
	Heating		kW	12.5	16.0	18.0
Power Input (Nominal)	Cooling		kW	2.81	3.51	4.53
	Heating		kW	2.74	3.86	4.57
EER				3.99	3.99	3.42
COP				4.56	4.15	3.94
Dimensions	(Height x Width x Depth)		mm	1,345x900x320		
Weight			kg	120		
Sound Level	Sound Power	Cooling	dB(A)	66	67	69
		Heating	dB(A)	50	51	53
	Sound Pressure	dB(A)	52	53	55	
Operation Range	Cooling	Min~Max	°CDB	-5~46		
	Heating	Min~Max	°CWB	-20~15.5		
Refrigerant				R-410A		
Power Supply				1N~/220-240V/50Hz		
Max n° of indoor units to be connected				6	8	9
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26 x 3		
Max total length			m	300		

HEAT PUMP				RXYSQ4P8Y1	RXYSQ5P8Y1	RXYSQ6P8Y1
Outdoor Unit (Three Phase)						
Capacity range			HP	4	5	6
Capacity	Cooling		kW	11.2	14.0	15.5
	Heating		kW	12.5	16.0	18.0
Power Input (Nominal)	Cooling		kW	2.89	3.61	4.65
	Heating		kW	2.82	3.97	4.69
EER				3.88	3.88	3.33
COP				4.43	4.03	3.83
Dimensions	(Height x Width x Depth)		mm	1,345x900x320		
Weight			kg	120		
Sound Level	Sound Power	Cooling	dB(A)	66	67	69
		Heating	dB(A)	50	51	53
	Sound Pressure	dB(A)	52	53	55	
Operation Range	Cooling	Min~Max	°CDB	-5~46		
	Heating	Min~Max	°CWB	-20~15.5		
Refrigerant				R-410A		
Power Supply				3N~/380-415V/50Hz		
Max n° of indoor units to be connected				6	8	9
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26 x 3		
Max total length			m	300		